

iSPOS 10



Wall Mount Capable



IP66 Whole Unit*



VESA Mount Capable

* Desktop type only

iSPOS S106/i106

Vast Potential in Limited Space

The iSPOS S106/i106 brings to you Senor's unparalleled quality and durability standard in a **compact-sized all-in-one** solution.

Its 10.4" high brightness, high resolution LED screen with multi-touch support offers the user comfort and ease on a fully functional surface. Powered by Intel® Quad Core Celeron / Dual Core i3 platform and fitted with SSD storage, the iSPOS S106/i106 exhibits **superior performance and reliability** to manage high volume transactions effectively.



A wide array of integrated options for seamless and wireless communication ensures the system is well connected.

The iSPOS S106/i106 can be implemented for a diverse range of applications in the retail, hospitality, banking and industrial sectors.

iSPOS S106/i106 WS

Sleek Wall Mount Panel PC

The wall mount solution, iSPOS/i106 S106 WS (IP54 rating) is ideally suited for sites with restricted space that require multiple access points for self-service activities.

Ideal application for

- Kitchen bump screen
- Guests check-In
- Membership registration
- Information operator
- Warehouse management
- Government facilities



Key Features



iSPOS S106/i106 WP Desktop Self Service Kiosk

The iSPOS S106/i106 WP (IP43 rating) is a compact sized, fully integrated desktop kiosk with an integrated thermal printer. It optimises an innovative modular construction design to simplify the maintenance process.

Ideal application for

- Self-service transactions
- Registration point
- Queue docket generation
- Ticket collection point



2-line VFD
(custom order)



8.4" LCD Customer Display
(custom order)



High Speed Thermal Printer
250mm/s



SPECIFICATIONS

	iSPOS S106	iSPOS i106
PROCESSOR	Intel Quad Core Celeron J1900 2.0 GHz	Intel Dual Core i3-6100U 2.3 GHz
SYSTEM MEMORY	4 GB DDR3L RAM (up to 8 GB)	4 GB DDR4 RAM (up to 32 GB)
STORAGE DEVICE	Half-slim SATA SSD	Half-slim SATA SSD

DISPLAY

SIZE / RESOLUTION	10.4" LED / 1024 x 768 pixels
BRIGHTNESS	400 cd/m ²
TOUCH SCREEN PANEL	Projected capacitive touch

I/O INTERFACE

USB PORT	4 x USB 2.0
SERIAL PORT	2 x DB9
VIDEO PORT	1 x VGA
AUDIO	2 x built-in speakers
ETHERNET PORT	1 x Gigabit LAN 10/100/1000 Mbps

OPERATING SYSTEM

WINDOWS	POSReady 7 / 7 Pro / 10 IoT / 10 Pro
---------	--------------------------------------

ENVIRONMENT & MECHANICAL SPECIFICATIONS

DIMENSIONS & WEIGHT	Desktop: 276 (W) x 230 (H) x 165 (D) mm 3.0 kg
	Wall Mount: 276 (W) x 223 (H) x 42 (D) mm 3.0 kg
	WP: 276 (W) x 405 (H) x 405 (D) mm 5.3 kg (with TP80 printer)
CHASSIS MATERIAL	Heat-dissipating solid aluminium die-cast casing with nano-coating technology
VESA PATTERN	75 x 75 mm / 100 x 100 mm
IP RATING	Desktop: IP66 Wall Mount: IP54 WP: IP43
TEMPERATURE	Operating: 0°C to 40°C Storage: -20°C to 60°C
HUMIDITY	Operating: 0% to 80% Storage: 10% to 90% (non-condensing)
POWER CONSUMPTION	12 V / 3.5 A, internal power adaptor, 100-240 V, 50/60 Hz

MODEL OPTIONS

INTEGRATED CARD READER	3-track MSR, RFID (125 kHz/13.56 MHz)
WIRELESS LAN	Wi-Fi 802.11 b/g/n

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

The Senor Building

65 & 67 Weaver Street
Coopers Plains
QLD 4108, Australia

www.senortech.com.au

P: +61 7 3275 5888
F: +61 7 3275 5800
sales@senortech.com.au

SENIOR
TOUCH SCREEN SOLUTIONS

Quality. Safety. Versatility.